



All Purpose Adhesive Caulk

DESCRIPTION

All Purpose Adhesive Caulk is a premium grade water-based caulk. This PVA based caulk was designed to have the strength of an adhesive and the sealing characteristics of a caulk. All Purpose Adhesive Caulk bonds to almost any surface including wood, concrete, metal, ceramic, drywall, plaster and much more. Easy to apply and tool. Environmentally safe, soap and water clean-up. Contains no silicone.

FEATURES

- Adhesive & Caulk in one
- Easy to apply & tool
- Soap & Water clean-up
- Low odor
- Remains flexible
- Cured caulk will resist mold and mildew growth.
- Weather-resistant seal
- Paintable

USES

All Purpose Adhesive caulk was designed to be a multiple use adhesive and caulk. Can be used for almost any household or remodeling project. Use for gluing loose molding or tiles, securing backsplashes, setting sinks and even repairing or concealing small cracks in plaster, drywall or around molding and baseboards. Polyseamseal All Purpose can even help to lower energy costs by sealing the air leaks around windows & doors and other utility & plumbing penetrations.

LIMITATIONS

- Apply at temperatures above 40°F(5°C) but below 120°F(49°C).
- Do not apply outdoors when rain or freezing temperatures are expected within 24 hours.
- Do not use for architectural joints, joints subject to heavy abrasion or wear, or tuck-pointing.
- Do not use below water line or aquariums, under shower door tracks or between non-porous surfaces.
- Do not use on mirrors or automotive finishes.
- If joint size should exceed 1/4" x 1/4" use backing material.

PACKAGING

12 – 10oz cartridges per case
12 – 6oz squeeze tubes per case
24 – 6oz squeeze tubes per case

COLOR OFFERING

10oz – White, Almond, Clear, Black, Bronze and Aluminum /Gray.
6 oz – White, Almond and Clear

COVERAGE

1/4" diameter bead: Approx. 30 lin. ft./10 oz cartridge

1/8" diameter bead: Approx. 122 lin. ft./10 oz cartridge

STORAGE

- Protect from freezing. Store between 40°F(5°C) and 100°F(38°C)
- Shelf life is 12 months (unopened)

APPLICATION PROCEDURES

Preparation

- Remove old caulk. Silicone remaining on surface will decrease adhesion.
- Clean thoroughly to remove dirt, grease, oil, wax, loose paint, dust and soap film.
- Remove mildew with bleach and detergent that does not contain ammonia. Rinse surface and allow to dry.

Directions:

- Cut tip on a slant to desired bead size.
- Insert cartridge in caulk gun.
- Apply steady pressure forcing caulk onto surface for a smooth bead.
- Smooth bead with wet finger or putty knife to desired appearance. Wipe off excess with damp cloth.
- Paintable in 2 hours, depending on temperature and humidity.
- Allow 24 hours before exposing to water.
- Periodically clean cured caulk with non-abrasive cleanser for best appearance.

Clean-up:

Clean tools and excess caulk with soap & water before caulk dries.

VOC-Colors <93g/l or 7.5%wt.

-Clear <2g/l or 1%wt.

CAUTION! KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

WARRANTY

OSI Sealants Inc. warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE NOT EXPRESSLY SET FORTH HEREIN. If not satisfied with the product's performance when used as directed, return sales receipt and used container to OSI Sealants Inc, 7405 Production Drive, Mentor, Ohio 44060 for product replacement.

For additional information, please contact Technical Services 1-800-624-7767.



OSI Sealants Inc.

A Subsidiary of
Sovereign Specialty
Chemicals, Inc.
Mentor, Ohio 44060

Made in USA

Phone: 800-624-7767

Fax: 440-974-8774

www.polyseamseal.com

sD20610